

# (agora)<sup>®</sup> PRO

EXPERIENCE FABRICS



MARINE VINYL

## ATLANTIS & ARGOS

# Atlantis



Royal Blue  
20002



Red  
20008



Turkis  
20004



Noir  
20009



Canary  
20011



Optik  
20007



Off White  
20005




Cream  
20003



White  
20013



Bone  
20010



Oat  
20006



Fossil  
20012


# Argos



Whisper  
20016



Silver  
20027



Pearl Grey  
20024



Cloud  
20025



Limestone  
20021



Integral  
20020



Coconut  
20017




Sand  
20026




Mineral  
20022


# Argos



Basalt  
20015



Graphite  
20018



Carbon  
20023

**(agora)<sup>®</sup>**



Indigo  
20019



Admiral  
20014



Billiard  
20029



Tirol  
20028

PVC Phthalate free  
PVC libre de ftalatos

www.agorafabrics.com

Performance fabrics of the highest quality created to maximize the relaxing and luxurious lifestyle of the modern aquaphile. Argos & Atlantis take Agora beyond its wildest adventures to places it hadn't reached before. An ideal choice for indoor and outdoor furniture in places of high traffic like spas, restaurants, poolside, and super yachts.

Tejidos de alto rendimiento de la más alta calidad creados para maximizar el estilo de vida relajante y lujoso del acuófilo moderno. Argos y Atlantis llevan a Agora más allá de sus aventuras emocionantes a lugares a los que no había llegado antes. Una opción ideal para muebles de interior y exterior en lugares de alto tráfico como spas, restaurantes, junto a la piscina y súper yates.



Composition Composición	80.82% PVC Phthalate free PVC libre de ftalatos 19.18% Polyester Poliéster
Weight Peso	730 g/m <sup>2</sup> 21.5 oz/yd <sup>2</sup>
Width Ancho	137 cm 54"
Length of rolls Longitud de las piezas	30 m 32.8 yd
Finish Acabado	Sanitized-Actifresh <sup>®</sup> Embossed Gofrado
Abrasion resistance Resistencia a la abrasión	>400.000 Martindale DIN EN ISO 12947-2:2016 >50.000 Wyzenbeek CFFA 1A
Flame resistance Resistencia a la llama	DIN 4102 B2 Önorm B 3825 Group 1 EN 1021 Parts 1 & 2 UNI 9175 Class 1/IM ÖNORM A 3800 Part 1 Class Q1 SAE J369/MVSS302 100mm/min. max IMO-MS-307(88) (FTP code 2010) Annex 1 Part 8 FAR 25/853 Appendix F Part I 10" FED-STD-191A Test 5903 6 in max.
Colour fastness to light Solidez a la luz	6/8 ASTM G154 UVA-340
Colour fastness to sea water Solidez al agua marina	4-5/5 DIN EN ISO 105-E02
Water column Columna de agua	>10.000 mm DIN EN 20811
Cleaning instructions Manutención	 Use neutral soap Utilizar jabón neutro
Uses Usos	

Sensitive values of tolerance +/- 7%. Valores susceptibles de tolerancia de +/- 7%

## Qualities Cualidades

									
WATERPROOF IMPERMEABLE	STAIN RESISTANT ANTIMANCHAS	MOULD RESISTANT ANTIMOHO	UV RESISTANT RESISTENCIA UV	DURABLE STRONG DURADERO	NO CONDUCTOR NO CONDUCTOR	EASY TO CLEAN FÁCIL DE LIMPIAR	DIMENSIONAL STABILITY ESTABILIDAD DIMENSIONAL	KID PROOF A PRUEBA DE NIÑOS	PET FRIENDLY APTO PARA ANIMALES

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.





**(agora)<sup>®</sup>**

Discover more at [www.agorafabrics.com](http://www.agorafabrics.com)